



- NOTES:**
- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.250" THK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC M6061T6S.250
 - 2) FINISH: ANODIZE BLACK PER MIL-A-8625F TYPE I OR IB OR IC OR II
OR IIB CLASS 2
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY PER DART QSI 044 6.3
 - 7) WEIGHT: 0.28 lbs
 - 8) ENGRAVE "DART" LOGO AND PART NUMBER BEFORE ANODIZING

PRELIMINARY ISSUE

A	NEW ISSUE	VS	15.09.28
REV.	DESCRIPTION	BY	DATE
DESIGN	VS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	VS		
CHECKED	RF	DRAWING NO.	REV. A5
MFG. APPR.	JLM	D5312	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		TIE DOWN BRACKET	NTS
DATE	15.09.28	COPYRIGHT © 2015 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	